



Mobil CVTF 3320

Multipurpose Continuously Variable Transmission Fluid

Product Description

Mobil CVTF 3320 is high performance, continuously variable transmission fluid designed to meet the service fill use for many Japanese designed vehicles. Mobil CVTF 3320 provides smoother, consistent all weather step-less shifting, and all-around lubrication protection of the transmission components to help extend transmission service life and provide a smooth driving experience.

Features and Benefits

Mobil CVTF 3320 is formulated from select high-quality base oils combined with an advanced additives system to ensure consistent repeatable, smooth, step-less shifts under a broad range of driving conditions, temperatures and transmissions. Key features and benefits include:

- Excellent thermal and oxidation stability for long and consistent transmission performance
- Optimized friction characteristics provides transmission efficiency and shifting performance
- Good film-strength and anti-wear properties reduce wear and maintain good transmission life
- Excellent low-temperature properties provide easier start-ups and improved lubrication at low ambient temperatures
- Effective foam control properties provide consistent shifting performance and reduce fluid losses in severe service
- Compatibility with all common seal materials helping the control of oil leakage

Applications

Mobil CVTF 3320 is recommended by ExxonMobil for refill of pulley-based continuously variable transmissions in Japanese designed vehicles, except for CVTs that require gear oils, and toroidal CVTs.

Specifications and Approvals

According to ExxonMobil, Mobil CVTF 300 is of the following quality level:

Toyota CVT-equipped vehicles	X
Daihatsu CVT-equipped vehicles	X
Suzuki CVT-equipped vehicles	Selected models
Mazda CVT-equipped vehicles	Selected models

According to ExxonMobil, Mobil CVT 300 is also of the following quality level: Nissan, Mitsubishi, Subaru, Suzuki and Mazda CVT-equipped vehicles, except where a gear oil or toroidal CVT is specified. Always consult your owner's manual to check specifications for your particular vehicle

Typical Properties

Mobil CVTF 3320

Viscosity, ASTM D 445	
cSt @ 40°C	31
cSt @ 100°C	7.1
Viscosity Index, ASTM D 2270	207
Brookfield Viscosity @ -40°C, cSt, ASTM D 2983	10,100
Flash Point, °C, ASTM D 92	192
Density @ 15 °C kg/l, ASTM D 4052	0.852
Color	Red

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil 1 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

7-2014

ExxonMobil Asia Pacific Pte Ltd
Jakarta Representative Office
Wisma GKBI 27th Floor
Jl. Jenderal Sudirman No. 28
Jakarta 10210
Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.