



## Mobil Coolant Extra Ready Mixed -24°C

### Extra High Performance Coolant

#### Product Description

Mobil Coolant Extra Ready Mixed -24°C is an extra performance coolant designed to provide efficient protection down to -24°C during winter condition. It is a ready to use product that has been premixed with 36% Mobil Antifreeze Extra and 64% water.

#### Features and Benefits

Mobil Coolant Extra Ready Mixed -24°C was developed to protect car, truck and bus engines of both ferrous and aluminium construction against corrosion and frost damage. It contains a blend of inhibitors designed to give a high degree of corrosion protection to engine components such as radiators, cylinder blocks/heads and water pumps over a 3 years period. Mobil Coolant Ready Mixed is free of nitrites, amines and phosphates

#### Applications

Mobil Coolant Extra Ready Mixed -24°C contains Glystantin from BASF. Glystantin® G48® by BASF is approved by:

Audi/Seat/Skoda/VW (vehicles built up until 1996) TL 774-C, Porsche (vehicles built up until 1995), Rolls-Royce (vehicles built as from 1998), BMW N 600 69.0, MAN 324 NF, Mercedes-Benz specification 325.0, MTU MTL 5048, Opel/Vauxhall (vehicles built up until 2000) B 040 0240, Saab 690 1599.

Pour into vehicle cooling system as recommended by vehicle manufacturer. Mobil Coolant Extra Ready Mixed -24° should not be mixed with silicate free, OAT engine coolants. Most coolant blends are based on carefully balanced mixtures of various corrosion inhibitors. Mixing of coolants with different inhibitor packages can lead to loss of corrosion protection.

#### Specifications and Approvals

##### According to ExxonMobil, Mobil Coolant Extra Ready Mixed -24°C is suitable for use in applications requiring:

Glystantin® G48® by BASF. Glystantin® G48® by BASF is approved by:

Audi/Seat/Skoda/VW (vehicles built up until 1996) TL 774-C	X
Porsche (vehicles built up until 1995)	X
Rolls-Royce (vehicles built as from 1998)	X
BMW N 600 69.0	X
MAN 324 NF	X
Mercedes-Benz specification 325.0	
MTU MTL 5048	X
Opel/Vauxhall (vehicles built up until 2000) B 040 0240	X
Saab 690 1599.	X

#### Typical Properties

##### Mobil Coolant Extra Ready Mixed -24

Color	Blue/Green
Density at 20°C, g/cm <sup>3</sup>	1.06

Boiling Point, °C	> 105
Flash Point, °C	> 120
pH value	7.5
Reserve Alkalinity (M10HCl), ml	5.5
Water Content, % max	65

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

8-2015

Mobil Oil Australia Pty Ltd  
A.B.N. 88 004 052 984  
12 Riverside Quay  
Southbank Vic 3006  
+61 3 8633 8444  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com). ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.