



## Mobil Super 1000 X2

### Premium Multigrade Passenger Vehicle Engine Oil

#### Product Description

The Mobil Super 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

#### Features and Benefits

Mobil Super 1000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 X2 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

#### Applications

Mobil Super 1000 products have been formulated to be suitable for use in nearly all vehicles. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

#### Specifications and Approvals

Mobil Super 1000 X2 meets or exceeds the requirements of: 15W-40		20W-50
API	SN/SM/SL/SJ	SN/SM/SL/SJ
ACEA	A3/B3	A3/B3

Mobil Super 1000 X2 has the following builder approvals: 15W-40		20W-50
MB-Approval	229.1	229.1

Mobil Super 1000 X2 is recommended by ExxonMobil for use in applications requiring: 15W-40		20W-50
API	CF	CF

#### Typical Properties

<b>Mobil Super 1000 X2</b>		
SAE Grade	15W-40	20W-50
Viscosity, ASTM D 445		
cSt @ 40° C	109	171
cSt @ 100° C	14.5	19.1
Viscosity Index, ASTM D 2270	136	127
Sulfated Ash, wt%, ASTM D 874	0.9	0.9
HTHS Viscosity, mPa•s @ 150° C, ASTM D4683	4.1	4.8
Pour Point, °C, ASTM D 97	-30	-27
Flash Point, °C, ASTM D 92	230	230
Density @15° C kg/l, ASTM D 4052	0.880	0.885

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

8-2015

Mobil Oil Australia Pty Ltd  
A.B.N. 88 004 052 984  
12 Riverside Quay  
Southbank Vic 3006  
+61 3 8633 8444  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com). ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.